

SECTION SF 30 BLOCK 14 CONTINUATION PAGE

SUMMARY OF CHANGES

SECTION SF 1449 - CONTINUATION SHEET

The purpose of this amendment is to correct the description in Line item 0033, by deleting this description in its entirety and replacing it with the following text:

ITEM NO
0033

Fire Fighting Pressure Hose in accordance with DIN 14811, Size B with Storz couplings, B75, 20m long, 100 % high tenacity synthetic yarn, circular woven (reinforced), embedded in a compact vulcanized rubber, high quality, special synthetic rubber on the basis of Nitrile/PVC, extruded through the weave, inside smooth for minimum friction loss, longitudinal ribs in the external covering for high abrasion resistance, heat resistant, resistant to oil and petrol, resistant to alkalies, acids, liquids, chemicals, ageing, ozone and UV rays resistant, temperature range from -35 to +80 Grad Celsius, with Imprint: FIRE-RESCUE-ANSBACH. Approvals: BS 6391, Type 3prEN 1924 Class4, MED 96/98 EC, SBG, MCA, TNO. Operating pressure: 15 bar. Testing pressure: 24 bar. Bursting pressure: over 50 bar -----COURTESY TRANSLATION----- B-Schlauch mit Storz-Kupplungen und Gummidichtung. Groesse: B-75, (75 mm Durchmesser), Laenge 20 m. aus 100% synthetischem Gewebe aus hochfesten Garnen, rundgewebt, eingebettet in Gummierung, Innen und Aussengummierung: hochwertiger Nitrilkautschuk, innen sehr glatt und aussen laengsgerippt, hohe Abriebfestigkeit, bestaendig gegen Laugen, Salzloesungen und Saeuren, alterungs, ozon und UV bestaendig, oel und benzinfest, Temperaturbestaendig von -35 bis 100 Grad Celsius, bestaendig gegen Seewasser, Rot gummiert mit Signierung fortlaufend: FIRE - RESCUE ANSBACH. Betriebsdruck: 15 bar. Pruefdruck: 24 bar. Zerplatzzdruck: ueber 50 bar. Zulassungen: BS 6391, Type 3prEN 1924 Class4, MED 96/98 EC, SBG, MCA, TNO.

(End of Summary of Changes)